



ZENIUS

THE COMPACT AND AGILE CARD PRINTER



The Zenius printer is designed for single sided printing of a very large variety of plastic cards. Zenius generates color or monochrome cards, individually or in small runs, with top quality results. Zenius is a user-friendly, compact and cost-effective solution for delivering your personalized cards.

FLEXIBILITY


- With Zenius, you can choose to insert your cards individually or with the automatic feeder.
- The «Expert» version of Zenius features combinable encoding functions: magnetic encoding, contact and contactless chips. It takes just a few minutes to install these modules!

EASE OF USE

- With the Evolis Premium Suite® software, you can receive notifications and easily control the printer from your computer.
- Evolis High Trust® ribbons are easy to install and automatically recognized and set by the printer.

SMALL FOOTPRINT

- Hardly larger than a standard sheet of paper, Zenius fits perfectly into any environment, be it the office or a customer service counter.
- Zenius is an eco-designed printer: very efficient sleep mode and low energy consumption.



MAIN FEATURES / Full technical specifications on www.evolis.com

GENERAL FEATURES

- Direct-to-card dye-sublimation/Resin thermal transfer
- Single-sided printing, edge-to-edge
- 300 dpi print head (11.8 dots/mm)
- 16 million colors
- 16 MB memory (RAM), 32 MB for the Expert version
- Colors available: fire red & grey brown

PRINTING PERFORMANCES

- Color (YMCKO): 120 - 150 cards/hour¹
- Monochrome: 400 - 500 cards/hour

INTERFACES

- USB (1.0, 1.1, 2.0, 3.0), cable supplied
- Ethernet TCP-IP 10BaseT, 100BaseT (Traffic Led) on the Expert version

CARD MANAGEMENT AND SPECIFICATIONS

- Automatic or manual feeding
- Feeder capacity: 50 cards (0.76 mm - 30 mil)
- Output hopper capacity: 20 cards (0.76 mm - 30 mil)
- Card thickness: 0.25 to 0.76 mm (10 to 30 mil), gauge adjustment
- Card types: PVC cards, composite PVC cards, PET cards, ABS cards¹, special varnished cards¹
- Card format: ISO CR80 - ISO 7810 (53.98 mm x 85.60 mm)

ADDITIONAL ENCODING MODULES

- Available modules on the Expert version:
 - Magnetic stripe encoder ISO 7811 HiCo/LoCo, JIS2
 - Smart contact station ISO 7816-2
 - Contact smart card encoder - PC/SC, EMV 2000-1
 - Contactless smart card encoder - ISO 14443A, B, ISO15693, MIFARE, DESFire, HID iCLASS
 - Other specific encoders upon request
- Internal USB ports
- Options can be combined
- Factory-installed or installed on site

SAFETY

- Support for Kensington® security lock
- Data encryption for magnetic encoding

DISPLAY

- Printer LEDs
- Graphical notifications from the printer²: cleaning alerts, empty/low level ribbon and card alerts, etc.

EVOLIS HIGH TRUST® RIBBONS

To maximize the quality and durability of printed cards, the lifespan of the print head and the overall printer reliability, use Evolis High Trust® ribbons.

- Automatic identification and setting
- Delivered in a drop-in cassette for easy handling
- Ribbon saver for monochrome printing

List of ribbons available on www.evolis.com

SOFTWARE

- Delivered with Evolis Premium Suite® for Windows®:
 - Printer driver
 - Evolis Print Center for administration and settings
 - Evolis Printer Manager for graphical notification³
 - 24/7 online support
- Compatible with Windows® (32/64 bits): XP SP3, Vista, W7, W8, W10
- Delivered with cardPresso XXS Lite for designing and editing badges:
 - Internal database up to 50 records
 - Windows® (from XP onwards) and Mac OS X
- Delivered with a driver for Mac OS X (from 10.5 onwards)
- Linux OS upon request
- Evolis Premium SDK for remote supervision of the printer, while facilitating and speeding up integration into IT systems

ECO-FRIENDLY DESIGN, CERTIFICATIONS AND STATEMENT OF COMPLIANCE

- Standby, sleep modes & reduced energy consumption
- CE, FCC, IEC, VCCI, CCC, KC, BIS, EAC
- RoHS

SIZE AND WEIGHT

- Size (H x W x D): 195 x 205 x 315 mm (7.68" x 8.07" x 12.4")
- Weight: 3.3 kg (7.3 lbs)

WARRANTY

- 2-year warranty (printer and print head)⁴
- Warranty extension available as an option

¹ Under specific conditions / ² Depends on the Windows® version / ³ Requires the .net 4.0 client profile version

⁴ Warranty subject to observance of specific conditions and use of Evolis High Trust® ribbons



CI Solutions
3625 Serpentine Drive
California
90720 Los Alamitos
United States
Tel : (562) 431-2594
Fax : (562) 493-2714
E-mail : sales@cardintegrators.com
Web : cardintegrators.com

US & CANADA

Evolis, Rising Sun Mills, 188 Valley St., Suite 421 - Providence, RI 02909
T: 401-751-5483 - F: 954-777-9267 - evolisnortham@evolis.com

HQ | EUROPE - MIDDLE-EAST - AFRICA - Angers - info@evolis.com

LATIN AMERICA - Miami - evolislatam@evolis.com

ASIA-PACIFIC - Singapore - evolisasia@evolis.com

CHINA - Shanghai - evolischina@evolis.com

JAPAN - Tokyo - evolisjapan@evolis.com

INDIA - Mumbai - evolisindia@evolis.com